

SPÉCIFICATIONS	ABC - HAUTE PERFORMANCES, POUDRE SÈCHE RÉGULIÈRE ET PURPLE K													
Type	Débit Rapide									Débit Conforme				
Produit	ABC			Régulier		Purple K				ABC		Purple K		
Grosueur & Cap.(lvs.)	13.2	20	30	20	30	13.2	20	20	30	20	30	13.2	20	30
(Kg.)	(6)	(9)	(13.6)	(9)	(13.6)	(6)	(9)	(9)	(13.6)	(9)	(13.6)	(6)	(9)	(13.6)
Numéro de Modèle	594	581	567	582	568	595	580	584	569	564	589	599	566	591
Classification U/L	2A : 40B :C	4A : 40B :C	4A : 40B :C	40B :C	40B :C	40B :C	40B :C	20B :C	40B :C	20A : 120B :C	20A : 160B :C	20A : 80B :C	120B :C	160B :C
Poids Transport (lvs.)	29	40	53½	40	56½	29	40	40	56½	40	56½	29	40	56½
Hauteur (po.)	17	24½	26¼	24½	26¼	17	24½	24½	26¼	24½	26¼	17	24½	26¼
Largeur (po.)	9½	9½	10½	9½	10½	9½	9½	9½	10½	9½	10½	9½	9½	10½
Diamètre (pc.)	7	7	8	7	8	7	7	7	8	7	8	7	7	8
Portée (pi.)	35 - 45			35 - 45		35 - 45				35 - 45		35 - 45		
Taux d'évac. (moy.)														
(lbs./sec.)	.95	1.33	1.42	1.33	1.76	.95	1.33	2.0	1.88	.66	.94	.67	.69	.88
Temps d'évac. (sec.)	14	15	21	15	17	14	15	10	16	30	32	22	29	34
Support Standard	Murale													